

REPRO SUPERFIX SPECIAL

Characteristics

Universal fixer concentrate for all standard graphic film and paper materials. Suitable for film developing machines and dip tank fixage. Short fixing times, good use with recycling equipment and low smell nuisance are the excellent properties of the concentrate.

Preparation

Line Films:

Dilution: 1 + 3

30 litres water + 10 litres concentrate make 40 litres ready-to-use fixing bath or regenerator.

Imagesetter Films:

Dilution: 1 + 3

30 litres water + 10 litres concentrate make 40 litres ready-to-use fixing bath or regenerator.

The ready-to-use solution in the replenishing tank has to be used up within 4 weeks.

Fixing conditions

The following fixing conditions are recommended:

Fixing bath temperature: max. 5°C under the developing temperature.

Fixing time: according to the material 25 or 35 seconds.

When using recycling equipment the following has to be noted: The silver contents should not fall below 0,3 g silver per litre at the process of silver recovery. At the silver recovery on the circulation the replenishing rate can be decreased about 70 %. At the discontinued silver recovery 10-20% of the volume should be exchanged against fresh fixing bath according to each partial silver recovery. The fixing times can extend.

Replenishment

The replenishment rate is 300 ml/m². The silver content in the fixing tank should not exceed 6 g silver per litre.

Packaging

REPRO SUPERFIX SPECIAL

10 l. conc. in PE-can

Art.-No. 106326